

This is a high gloss clear cast vinyl film with a polyester liner which can be used for overlaminating other vinyl films

Features:

- >The superb clarity of the cast vinyl film and of the acrylic adhesive are enhanced by the smooth polyester liner to keep the image sharp and clear.
- >The overlamine adhesive wets out quickly to provide a clean image.
- >The stabilized vinyl film offers excellent protection from UV radiation to enhance the weathering of the underlying graphics.
- >The cast vinyl film offers the maximum flexibility.

TECHNICAL DATA

Face Material: 2 mil premium cast vinyl
 Color and Finish: Clear – Gloss
 Adhesive: Permanent acrylic
 Release Liner: 1.2 mil polyester

Typical Characteristics

Average Adhesion Values	20 min.	24 hr.
(PSTC-1, 180° peel @ 12"/min., 73°, on stainless steel)	32oz/in.	50oz/in.
Minimum Application Temperature:	50°F	
Service Temperature Range:	-50°F to 225°F	
Peak Value		

Shelf Life @ 73°, 50% RH:	2 years
Dimensional Stability (48 hrs. @ 150°F)	0.01 inches
Outdoor Life of film:	5 years
60° Gloss	80 minimum

Chemical Resistance

Distilled Water (24 hours)	No Effect
Detergent (24 hours)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (10 minutes)	No Effect
SAE 30 Motor Oil (10 minutes)	No Effect

Applications:

>Overlaminates for your digital media

Available Sizes:

Finished Rolls	Core	Print Side
38" X 150'	2"	PSO
38" X 150'	2"	PSO
54" X 150'	2"	PSO
60" X 150'	2"	PSO