

Clear polyester with permanent adhesive on each side combined with a 1.5-mil polyester liner on each side for excellent clarity. This clear mounting film is designed for laminating permanently to printed substrates.

Features:

>Permanent acrylic on both sides with high peel and good tack.

Technical Data

Face Material	1.0-mil clear polyester
Color and Finish	Clear
Adhesive	22, permanent solvent acrylic each side
Liner	1.2-mil polyester each side

TYPICAL CHARACTERISTICS

Target Adhesion Values	15 min.	24 hr.
(PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	40 oz.	45 oz.
Static Shear	> 24 hours	
(1/2-inch x 1/2-inch x 500 grams)		
Minimum Application Temperature Range	50°F to 120°F	
Service Temperature Range	-65°F to +225°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability	2 years	

CHEMICAL RESISTANCE

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Anti-Freeze (24 hr)	No Effect
SAE 20 Motor Oil (24 hr)	No Effect
Gasoline (1 hr)	No Effect

Disclaimer: The information supplied in this technical sheet is for guidance only and should not be construed as warranty of any kind. This document is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice. Please contact *Media One Digital Imaging Solutions, LLC* for any additional information you may require.

Applications:

- >Adhering nameplates and backlit panels
- >Point of purchase displays
- >Promotional products

Available Sizes:

Finished Rolls	Core	Print Side
38" X 150'	2"	PSO
51" X 150'	2"	PSO
54" X 150'	2"	PSO
60" X 150'	2"	PSO