

This is a 1 mil clear Tedlar® Anti Graffiti overlaminating film. This product is designed for use as a protective over laminate where graphics may experience a high exposure to scuffing. This over laminating film adds depth to the aesthetics of visual images such as photo displays and point-of-purchase graphics.

Features:

> Impact resistant.

Technical Data

Face Material:	1 mil Tedlar®
Color and Finish:	Clear
Adhesive:	Permanent Acrylic
Release Liner:	50 gsm glassine white

Typical characteristics

Average Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F on stainless steel)	15 min.	24 hr.
	2.9 lbs/in	3.8 lbs/in
Minimum Application Temperature:	50°F	
Service Temperature Range:	-65°F to 225°F	
Shelf Life @ 73°, 50% RH:	2 years	
Outdoor Life	Up to 5 years	
UV Block (spectrophotometer)	100%	200 nm – 360 nm
	56%	360 nm – 400 nm

Chemical Resistance

Distilled Water (24 hours)	No Effect
Detergent (24 hours)	No Effect
10% HCl (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect

Applications:

> Ideal Lamination for Anti Graffiti Applications

Available Sizes:

Finished Rolls	Core	Print Side
38" X 150'	2"	PSO
54" X 150'	2"	PSO

Disclaimer: The information supplied in this technical sheet is for guidance only and should not be construed as warranty of any kind. This document is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice. Please contact *Media One Digital Imaging Solutions, LLC* for any additional information you may require.