

Ideal for temporary and short-term durability (6 months). This overlamine product is an excellent choice for economical floor graphics applications. This product is offered on a film liner for excellent wet out and is UL-410 classified for slip resistance.

Features:

- >UL-410 classified for slip resistance
- >Environmentally friendly
- >Clear textured

Applications:

- >Floor graphics
- >Point of purchase displays
- >Counter graphics

Technical Data

Face Material	3.75-mil polyolefin
Color and Finish	Clear textured
Adhesive	FG, overlaminating permanent acrylic
Liner	1.2-mil clear film

Typical Characteristics

Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73°F, on Stainless Steel)	<u>15 min.</u> 65 oz.	<u>24 hr.</u> 75 oz.
Minimum Application Temperature	50°F	
Service Temperature Range	-40°F to +180°F	
Shelf Life (@ 73°F, 50% RH)	2 years	
Outdoor Durability	Indoor use only	

*Edge sealer can be applied to protect the edges of your graphics from potential lifting and curling that occurs from contamination or cleaning. The sealer should be tested to determine suitability with overlamine.

Chemical Resistance

Distilled Water (24 hr)	No Effect
Detergent (24 hr)	No Effect
10% HC1 (10 min)	No Effect
10% Ammonium Hydroxide (10 min)	No Effect
Gasoline (1 hr)	No Effect

Disclaimer: The information supplied in this technical sheet is for guidance only and should not be construed as warranty of any kind. This document is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice. Please contact *Media One Digital Imaging Solutions, LLC* for any additional information you may require.