

Applications:

- Banners
- Blockout

Material details:

CHARACTERISTICS	DATA	TEST METHOD
Weight	13oz/440gsm	ISO3801:1977
Polyester Fabric	250x250 denier 36x36fd per inch	DIN60001/DIN EN ISO2060
Type of Coating	PVC	N/A
Tensile Strength	1100N/5cm (L)	ISO527/3:1995
	900N/5cm (W)	
Tear Strength	80N/5cm (L)	ISO4674/1:2003
	70N/5cm (W)	
Adhesion Strength	60N/5cm	DIN53357:1982
Low Temperature	-22°F / -30°C	ISO13934-1:1999
RF Weldable (Heat Sealable)	YES	DIN53354

Ink Comptibility:

- UV
- Latex
- Solvent
- Eco Solvent
- Screen Printing



CERTIFIED FOR HP LATEX INKS

Disclaimer: The information supplied in this technical sheet is for guidance only and should not be construed as warranty of any kind. This document is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice. Please contact *Media One Digital Imaging Solutions, LLC* for any additional information you may require.