



This is a 3.4-mil premium clear gloss flexible calendared PVC film coated with permanent acrylic pressure sensitive adhesive laminated to a layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems. Adhesive produces permanent bonds to a variety of common substrates used in graphics applications. The liner offers excellent product layflat in common ambient conditions.

Technical Data

<b>Thickness</b>	Film            3.4 mils. Adhesive      .8 to 1.0 mils. Liner           6.7 mils. (Thickness variance +/- 10%)
<b>Dimensional Stability</b>	Good.
<b>Temperature Ranges</b>	Minimum application temperature is +40°F. Service temperature is -40°F to +180°F.
<b>Expected Exterior Exposure</b>	Clear vinyl film can yellow with exposure to UV radiation. Must be tested for specific usage.
<b>Adhesion</b>	To stainless steel – 48 oz/in. PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
<b>Water Resistance</b>	Limited immersion resistance. Test for specific application. If using the wet application method the product may fog when exposed to water. This condition will usually clear within 48 hours at normal temperature and humidity.
<b>Humidity Resistance</b>	Good. Under high humidity conditions product may fog. This condition will usually clear within 48 hours at normal temperature and humidity. 6-months shelf life when stored at 70°F and 50% relative humidity.
<b>Storage Stability</b>	

**Recommendations:** Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.

Applications:

>This is designed for interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.

Available Sizes:

Finished Rolls	Core	Print Side
54" X 150'	2"	PSO
60" X 150'	2"	PSO