



This is a 3-mil premium white gloss flexible calendared vinyl film coated with removable acrylic pressure sensitive adhesive laminated to a 90 gsm layflat liner. This film is designed to accept a variety of solvent-based inkjet and UV curable inks common to wide format digital printing systems.

Technical Data

Thickness	Film	3.0 mils. .8 to 1.0
	Adhesive	mils.
	Liner	6.7 mils. (Thickness variance +/- 10%)
Dimensional Stability		Good.
Temperature Ranges		Minimum application temperature is +40°F. Service temperature is -40°F to +180°F.
Expected Exterior Exposure		Removable up to 1 year under normal conditions.
Adhesion	To glass	5 to 15 oz. /in.
	To standard test panels	5 to 15 oz. /in.
		Tested according to PSTC-1 with 24-hour dwell at 70°F and 50% relative humidity. Typical values. Individual values may vary. Test thoroughly before production.
Water Resistance		Good. Test if immersed.
Humidity Resistance		Good.
Solvent Resistance		Good 6 months shelf life when stored at 70°F and 50% relative humidity.
Storage Stability		Completely evaporate inkjet solvents before application. Failure to do so may facilitate solvent penetration resulting in vinyl degradation.
Recommendations		

Applications:

>This is designed for temporary interior or exterior signage, decals, nameplates, die-cut letters and point-of-purchase displays.

Available Sizes:

Finished Rolls	Core	Print Side
54" X 150'	2"	PSO
60" X 150'	2"	PSO