

**3.5mil Matte Hybrid Blockout Vinyl**

A premium 3-year outdoor durable matte white vinyl media with permanent High Bond Gray adhesive for mounting to boards and other hard to adhere to substrates. Excellent for use on Acrylic, Steel and painted dry wall for medium-term promotional, point of purchase, trade show displays, outdoor signage and banners.

**Features:**

- >3-year outdoor durable matte white vinyl
- >High Bond Gray adhesive

**TECHNICAL DATA**

Face Material: 3.2-mil flexible vinyl  
 Color and Finish: White matte  
 Adhesive: Permanent acrylic High Bond Gray  
 Liner: 72# polycoated bleached kraft

**TYPICAL CHARACTERISTICS**

| Target Adhesion Values<br>(PSTC-1, 180° peel @ 12"/min., 73°F, on:) | 15 min.         | 24 hr.       |
|---|-----------------|--------------|
| Stainless Steel   | 60 oz. /inch    | 80 oz. /inch |
| Polyethylene  | 45 oz. /inch    | 60 oz. /inch |
| Polypropylene   | 50 oz. /inch    | 65 oz. /inch |
| Gatorplast™   | 60 oz. /inch    | 75 oz. /inch |
| Gatorfoam®  | 45 oz. /inch    | 60 oz. /inch |
| Sintra®   | 60 oz. /inch    | 65 oz. /inch |
| Diebond ®   | 75 oz. /inch    | 85 oz. /inch |
| Acrylic   | 80 oz. /inch    | 85 oz. /inch |
| Glass   | 70 oz. /inch    | 85 oz. /inch |
| Minimum Application Temperature                                     | 50°F            |              |
| Service Temperature Range   | -40°F to +180°F |              |
| Shelf Life (@ 73°F, 50% RH)   | 1 year          |              |
| Outdoor Durability  | 3 years         |              |

**CHEMICAL RESISTANCE**

|                                 |           |
|---------------------------------|-----------|
| Distilled Water (24 hr)         | No Effect |
| Detergent (24 hr)               | No Effect |
| 10% HCl (10 min)                | No Effect |
| 10% Ammonium Hydroxide (10 min) | No Effect |
| Anti-Freeze (24 hr)             | No Effect |

Disclaimer: The information supplied in this technical sheet is for guidance only and should not be construed as warranty of any kind. This document is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice. Please contact *Media One Digital Imaging Solutions, LLC* for any additional information you may require.

SAE 20 Motor Oil (24 hr)  
Gasoline (1 hr)

No Effect  
No Effect

**Applications:**

- >Indoor Signage
- >Photo Advertisement
- >Photos and Graphics Displays