

Malibu™

Product Code	Construction	Material	Weight	Thickness	Max Width
TX-Illuminate Premium	Woven	100% Coated PES	6.88 oz/sq.yd	0.23 mm	197 in.
TX-Illuminate Premium-RY	Woven	100% Recycled PES			
TX-Illuminate Premium-AM	Woven	100% Uncoated PES			

Description

Woven Water Proof Fabric with light diffusion coating for Backlit and Tent

Features

One Side Coated for Solvent an UV, Frontlit or Backlit, High quality backlit images

Applications

White Backed SEG | Crease Free Backlit SEG | Lightbox

Ink Compatibility

UV | Latex

Print Side

Sublimation | Both

Shrink (l):

Shrink (w):

Stretch (l): .80%

Stretch (w): .80%

Stretch at Burst (l): 24.00%

Stretch at Burst (w): 21.00%

Burst Strength (l): 266 lbs/in

Burst Strength (w): 232 lbs/in.

Tensile Strength (l): 11 lbs/in

Tensile Strength (w): 10 lbs/in.

Burst Strength: 281 lbs

Yellowing: 0.00dE

Max Roll Length: 100m

Available Recycled: Yes

P 238749:

Fabrics: Coated Knitted fabrics-

100% Recycled post-consumer

Made with 100% Plastic Bottles

Available Anti-microbial: Yes



NFPA-701 flame Retardant certified.

Recommended transfer settings for sublimation are
374°F-410°F for 40-100 seconds at 40psi.