

Rincon™

Product Code	Construction	Material	Weight	Thickness	Max Width
TXRV	Knitted	100% Coated PES/FR	6.53 oz/sq.yd	0.30 mm	126 in.
TXRV-RY	Knitted	100% Recycled PES			
TXRV-T	Knitted	100% Uncoated PES			

Description

Dual Sided Fabric for Tradeshow and Display Graphics

Features

Dual Finishes

Applications

SEG Graphics, Tradeshow, Table Throws

Ink Compatibility

Dye Sub Transfer | Dye Sub Direct | UV

Print Side

Sublimation | Both

Shrink (l):

—

Shrink (w):

—

Stretch (l):

1.00%

Stretch (w):

0.60%

Stretch at Burst (l):

44.00%

Stretch at Burst (w):

29.00%

Burst Strength (l):

364 lbs/in.

Burst Strength (w):

299 lbs/in.

Tensile Strength (l):

13 lbs/in.

Tensile Strength (w):

15 lbs/in.

Burst Strength:

344 lbs

Yellowing:

1.17 dE

Max Roll Length:

m

Available Recycled:

Yes

Available Anti-microbial:

Yes



All fabrics are NFPA-701 flame Retardant
Certified/B1 M1 Certifications Available on Request.
Recommended transfer settings for sublimation are
374°F-190°C°F for 40 seconds at 40psi.