



Silver Strand™

Product Code	Construction	Material	Weight	Thickness	Max Width
TXSFL	Woven	100% Polyester	1.91 oz/sq.yd 65 GSM	0.1 mm	126 in.
TXSFL-RY					
TXSFL-AM					

Description  
Silver Liner

Features  
Lightweight, Economical Blockout Liner, Sew In Liner

Applications  
Flag Liner | Multi-Layer Liner | Specialty Applications

Ink Compatibility  
Non-Printable

Cutter Compatibility  
Any

Shrink (l):	—	
Shrink (w):	—	
Stretch (l):	0.40%	LOW
Stretch (w):	0.80%	LOW
Stretch at Burst (l):	21.00%	LOW
Stretch at Burst (w):	16.00%	LOW
Burst Stregth (l):	136 lbs/in.	LOW
Burst Strength (w):	89 lbs/in.	LOW
Tensile Strength (l):	4 lbs/in.	LOW
Tensile Strength (w):	4 lbs/in.	LOW
Burst Strength:	138 lbs	LOW
Yellowing:	_ dE	
Max Roll Length:	_m	
Available Recycled:	No	
Available Anti-microbial:	Yes	



NFPA-701 flame retardance certified.  
Recommended transfer settings for sublimation are  
374°F-410°F for 40-100 seconds at 40psi.