

## Trussels™

Product Code	Construction	Material	Weight	Thickness	Max Width
TXTF	Woven	100% Coated PES/FR	2 oz/sq.yd	0.48 mm	126in.
TXTF-RY	Woven	100% Recycled PES			
TXTF-T	Woven	100% Uncoated PES			

## Description

Curtain

## Features

Transparent, Very Good Print Through

## Applications

Flags | Beach Flags | Banners | Projection Backs

## Ink Compatibility

Dye Sub Transfer | Dye Sub Direct

## Print Side

Sublimation | Both

<b>Shrink (l):</b>	1.83%
<b>Shrink (w):</b>	0.67%
<b>Stretch (l):</b>	2.13%
<b>Stretch (w):</b>	2.27%
<b>Stretch at Burst (l):</b>	50.00%
<b>Stretch at Burst (w):</b>	40.00%
<b>Burst Strength (l):</b>	287 lbs/in.
<b>Burst Strength (w):</b>	224 lbs/in.
<b>Tensile Strength (l):</b>	12 lbs/in.
<b>Tensile Strength (w):</b>	11 lbs/in.
<b>Burst Strength:</b>	263 lbs
<b>Yellowing:</b>	0.62 dE
<b>Max Roll Length:</b>	100m
<b>Available Recycled:</b>	Yes
<b>Available Anti-microbial:</b>	Yes



All fabrics are NFPA-701 flame Retardant  
Certified/B1 M1 Certifications Available on Request.  
Recommended transfer settings for sublimation are  
374°F-190°C°F for 40 seconds at 40psi.