

Ventura

Product Code	Construction	Material	Weight	Thickness	Max Width
TXV-126	Woven	100% Coated PES/FR	3.0 oz/sq.yd	0.40 mm	126 in.

Description

Lightweight Sheer Fabric for Indoor Use

Features

Transparent, Very Good Print Through, Standard: Single Boxing Package

Applications

Banners | Curtain Decorations

Ink Compatibility

Dye Sub Transfer | Dye Sub Direct | UV | Latex

Print Side

Sublimation | Outside

Shrink (l):	—
Shrink (w):	—
Stretch (l):	0.40%
Stretch (w):	0.40%
Stretch at Burst (l):	32.00%
Stretch at Burst (w):	17.00%
Burst Strength (l):	468 lbs/in.
Burst Strength (w):	230 lbs/in.
Tensile Strength (l):	18 lbs/in.
Tensile Strength (w):	15 lbs/in.
Burst Strength:	308 lbs
Yellowing:	2.22 dE
Max Roll Length:	150m
Available Recycled:	Yes
Available Anti-microbial:	Yes



All fabrics are NFPA-701 flame Retardant Certified/B1 M1
Certifications Available on Request/B1 M1 Certifications Available on
Request

Recommended transfer settings for sublimation are
374°F-190°C°F for 40 seconds at 40psi.